

Your order consists of digitally printed Floor Graphics: printed media is 2mil. adhesive backed vinyl with a 10mil. UL slip resistant laminate on a 90lb. backer. On most floor graphics, due to the mil. thickness of the digital media and lamination, you will observe **Channeling** (separation from printed media and lamination from the backer paper) on the front (printed side.) Please **do not be concerned** when you observe this action, as it is due to rolling the graphics. Once you position the film to your substrate (floor) and begin removing the backer from the printed media, the vinyl **will** relax and lay flat on your substrate.

PREPARATION

Clean the area in which the Floor Graphics will be applied: It is **recommended** to use 99% Alcohol to remove dirt and surface wax. **Allow the Alcohol to evaporate.** Re-clean the area with standard foam window cleaner that is ammonia free. **Allow it to dry.** Position your graphics. If your order required **panels** (additional prints to complete the entire image), align each panel in sections according to the markings on the backer (Panel A to Panel 1.) **Most panels are printed with a 1" overlap**, therefore you will need to align all panels to assure the graphics will match from panel to panel. Once this process has been completed, you may begin installing your first panel. You will need to **tape** the top leading edge of the panel to the floor (3M masking tape works very well.) Apply half of the tape width on the top side of the print with the second half on the floor. Make multiple rolls of this process to have the panel secured to the floor to **prevent movement**. Upon completion, flip the panel over from the bottom to the taped top to locate the edge of the backer and **slowly** begin pulling the backer down carefully. Do **not** allow the media to make contact with the surface during this process. Remove at least 12" of backer from the media, then **slowly** pull the media back over where you can see the complete top side of your graphics. Remember not to allow the media that you have removed from the backer to make contact with the floor. Once you have the full image back in position, you may begin to **squeegee** the print to the floor using a left to right motion across the face of the print. As you squeegee the print, slowly reach underneath the print and pull the back away from the media exposing the adhesive side. Continue this process until the entire panel is applied.

MULTIPLE PANELS

Install the second panel in the **same manner** with one **exception**: you **must** align the second panel to the first panel on the top and also on the leading edge. First position the panel on the top and then move the panel left or right to **match** the graphics on panel one. Once this has been complete, hinge the top and **repeat** the installation process. You **must** follow this process on each panel to ensure all panels are matched and applied.