

STEP EIGHT

After the initial drying period has elapsed you are ready to coat the wall and Wall Covering with your **glue**. We recommend using a **clay** base adhesive, **Roman Pro 732** (this can be found at a Lowe's, Sherwin Williams or similar store.) Using a member of your installation team, **coat** the wall using a standard tight nap roller. Spread the adhesive thin and evenly. While this is being done, other team members need to layout **protective sheeting** on the floor (to protect the carpet from adhesive) and roll adhesive on the back side of the wall panel thin and evenly. Be sure to apply adhesive on the **edges**. Once the coating of the adhesive on the panel has been completed **book** the panel (fold in half, adhesive to adhesive for three to four minutes.) Do not be concerned with drying at this time on the wall surface or panel, because you are using a clay base water adhesive and it dries **slowly**.

STEP NINE

After the initial drying period has elapsed, take the **booked** panel to the wall area. Grabbing from the **top corners**, place the panel at the top of the wall. Keep the panel from making contact with the wall surface that has **adhesive** applied. Extend the panel to full length, now apply the panel to your wall. Square the top and edge plum. Remember your next panel has to fit tight (**butt joint**.) Using a standard **wall covering brush** (found at any hardware store.) Wrap the entire brush and bristles in a **damp** soft towel. Begin squeezing the panel until the entire panel is against the wall. Be sure to **slowly** without too much pressure push as many as the **air/glue pockets** out. Generally working at the top going left to right and slightly downward as you progress until reaching the bottom. Repeat this process again. Once the panel is on the wall and as a team member is working the panel down, other team members should be coating out another panel following step eight. When the wall panel is completed, the second panel should be ready to be installed. **Continue this process until all panels are completed.**

STEP TEN

As you are applying the next panel, you will be required to place the panel **tight** with the first to create a tight butt joint. If you are **matching** art or lettering, **adjust** the panel so all will **align** properly. To ensure an **invisible** or **almost invisible** seam, it is best to take your index fingers and **push panel one seam** toward **panel two seam** to achieve a tight butt joint. Almost to the point that the two panels create a small peak. You **may** observe finger impressions in the material, **do not** become concerned as you will **smooth** these impressions out at the end of your installation. Do not push down the seam joint. Allow this area to dry a little longer. Move to the next butt joint and repeat.