

## STEP ELEVEN

Now all of your wall panels **should** be installed. Using a **soft damp cloth**, you need to wash any **excess** adhesive glue **off** the face of your Wall Covering. It is best to have **multiple** pails of clean water available. Rinse and change out your cloths as any glue residue remaining in your cloth will **leave** residue on the wall covering. As you are cleaning the surface area do **not** push hard as you can discolor the Wall Covering. If you encounter extreme glue on the face and it appears not to be cleaning well, use the moisture from the cloth to soften the glue and then wipe clean.

## FINISHING

Using a four inch hard standard wall paper roller, now you need to **go over** the butt joints and **push** all the seams down and tight. Push the front outside of each panel in toward the seam, pushing and depressing excess glue and finger impression to a minimum. You will **not** be able to remove all impressions. **Trim** any excess Wall Covering on edges, top, door jams and base cover. **Review** your installation and **check** one final time for any glue residue on the face and wipe/clean with damp cloth. Do **not** attempt to dry the moisture, it will dry on it's on. As you review your installation you will **notice** dimples/impressions throughout the Wall Covering. **Inform your client**, these **will** go away. Using a clay base adhesive takes time to **evaporate**. It is a process, but as it is drying it is pulling the material tight and snug against the wall. Expect a **minimum** of at least 3 days and a **maximum** of up to two weeks for it to cure completely. Once it cures, your wall covering is clean from impressions and extremely flat.