

Aluminum Street Graphics **easily** apply directly to an infinite variety of surfaces including sealed and unsealed concrete, asphalt, brick, tile, terrazzo, marble, and vinyl flooring plus vertically on brick, stucco, cinder-block and other exterior masonry wall surfaces.

SURFACE PREPARATION

The surface **must** be clean and thoroughly dry for proper performance. Usually, thorough sweeping is sufficient, but if the surface is oily, it **may** need to be power washed with a commercial degreaser. **Avoid** applying over loose or caked dirt, gravel, oily residues, flaking paint or other foreign substances that will interfere with proper bonding.

STANDARD APPLICATION

Recommended surface temperature **should** be 32 degrees Fahrenheit or higher. Sweep dry surface clean of dirt & debris. Peel off the backing paper (**release liner**) from the pressure sensitive adhesive. Lay down flat on the selected location. Smooth by hand from the center to outer edge, be sure all edges lay **flat** then firmly press down, step on or use any type of roller to compress to the surface. Make sure all edges are **completely** adhered. Large scale graphics should be tiled edge to edge with **no** overlapping.

ROUTINE MAINTENANCE

Wet the Aluminum Street Graphic and sweep with a broom; **avoid** harsh cleaning chemicals to extend the product life. Aluminum Street Graphics can withstand limited power washing, intense power washing **can** cause the edges to come loose. To **avoid** risk of trip hazard injury, **immediately** remove graphics if any edge of the graphic lifts and replace with a new graphic.

REMOVAL

Generally easy to remove on wall and pedestrian walkway applications; rough surfaces and/or vehicular traffic **may** increase the difficulty in removal. Simply peel off at an angle less than 45 degrees for **best** result; typically leaves no residue. Use power washer at a low angle to remove well-worn graphics. Severely worn-in graphics on rough textured surfaces **may** require a combination of scrubbing with wire bristle brush and rinsing from hose or power washing. If there is adhesive residue; remove with cleaning solvents, mineral spirits or burn with gas flame. Green Credentials: contains no PVC or hazardous ingredients; dispose with aluminum recycling. ****Important: graphics placed on asphalt or other rough surfaces in locations where heavy vehicle traffic is present could be difficult to remove.****